

06 VÁLVULA DE PIE PVC - CIERRE CLAPETA



PVC SWING FOOT VALVE



CONSTRUCCIÓN / MATERIALS

- 1 - Pasador: **AISI 304**
Lock: *AISI 304*
- 2 - Soporte: **ABS**
Support: *ABS*
- 3 - Clapeta: **ABS**
Flanges: *ABS*
- 4 - Tornillos: **AISI 304**
Screws: *AISI 304*
- 5 - Soporte clapeta: **ABS**
Disc support: *ABS*
- 6 - Junta: **EPDM**
Joints: *EPDM*
- 7 - Junta tórica: **EPDM**
O-ring: *EPDM*
- 8 - Cuerpo: **PVC**
Body: *PVC*
- 9 - Tornillo: **AISI 304**
Screw: *AISI 304*
- 10 - Brida: **PVC**
Flange: *PVC*
- 11 - Filtro: **PVC**
Filter: *PVC*




CONDICIONES DE TRABAJO / OPERATING CONDITIONS


- Temperatura máx.: **60°C**
Maximum temperature: *60°C*
- Presión máxima de servicio: **10 bar**
Max. service pressure: *10 bar*



DN 65-150



DN 200



DN 250

DIMENSIONES (mm) / Dimensions (mm)

Código Code	Medida Size	DIN					
		Ø P.C.D.	ØM	n-ØH	T	L	ØD
AA 06 381	DN 65	145	185	4-Ø18	23	283.5	67
AA 06 382	DN 80	160	200	8-Ø18	24	310	80
AA 06 383	DN 100	180	220	8-Ø18	24	348.5	102
AA 06 384	DN 125	210	250	8-Ø18	24	424.5	124
AA 06 385	DN 150	240	285	8-Ø23	26	490	145
AA 06 386	DN 200	295	360	8-Ø22	36	580	198
AA 06 387	DN 250	350	406	12-Ø23	42	584	198

