

DIGITAL THERMOSTATS



HD-210 model

- Permanent temperature override.
- Operate as a thermometer in OFF mode.
- Heating or cooling is selectable by switch option.
- Short cycle delay for cooling.
- Battery operate (3VDC) only two external wires are connected.
- External temperature sensor is also available (optional).
- Preset °C or °F display.

Specification:

- Temperature range: 5-30°C.
- Differential: $\pm 0.5^\circ\text{C}$ from Set temperature.
- Batteries: 2 x AA size batteries (Alkaline recommended).
- Rated switching power: 250V, 5A, resistive load or 2A inductive load
- Minimum On time in head mode: 1 minute
- Minimum Off time in cool mode: 3 minutes
- Battery low: Thermostat will turn Off and low battery indication will show on display.
- Size: 114 mm x 75 mm x 30 mm.



Part num.: CO 14 550

HP-510 model

- Pre-set 7 days programs.
- Easy to change pre-set programs.
- Manual temperature override.
- Permanent temperature override.
- Both time and temperature (room and set) permanently showing on the display.
- Adjustable differential by internal pins.
- Short Cycle delay for cool mode.
- Operate by 2 X AA size batteries.
- Heat and Cool selected internal pins.
- Holiday mode.
- Antifreeze 7°C

Specification:

- Temperature range: 5-30°C.
- Differential: $\pm 0.5^\circ\text{C}$ from Set temperature (optional $\pm 0.2^\circ\text{C}$).
- Temperature accuracy: $\pm 0.5^\circ\text{C}$.
- Rated switching power: 250V, 5A, resistive load or 2A inductive load
- Min On time in head mode: 1 min.
- Min Off time in air-conditioning mode: 3 min.
- Size: 130 mm x 84 mm x 30 mm.



Part num.: CO 14 555